



Araldite® 2011

Application	Bonded assembly of transparent door handles, eliminating the displeasing visual effect of the threaded couplings and rivets
Substrates bonded	Glass to metal
Pretreatments	Simple degreasing
Design of joint	Cylindrical
Curing conditions	Ambient temperature
Special service conditions	Repeated stresses are applied to the joint during use
Advantages for the customer	Easy application, giving shorter production times, and consequently reduced costs, in addition to the aesthetic effects of bonding vs mechanical fixing
Advantages over competition	Convenient and easy to use
Araldite® Adhesive used	Araldite® 2011
Customer location	Italy

Fast Facts

Two component epoxy paste adhesive

Multi purpose

Long working life

Low shrinkage

Good resistance to dynamic loading

Bonds a wide variety of materials in common use

Ideal for bonding:

- polyamides
- GRP
- ABS
- metals
- ceramics

Statements in this release that are not historical are forward-looking statements. These statements are based on management's current beliefs and expectations. The forward-looking statements in this release are subject to uncertainty and changes in circumstances and involve risks and uncertainties that may affect the company's operations, markets, products, services, prices and other factors as discussed in the Huntsman companies' filings with the Securities and Exchange Commission. Significant risks and uncertainties may relate to, but are not limited to, financial, economic, competitive, environmental, political, legal, regulatory and technological factors. Accordingly, there can be no assurance that the company's expectations will be realized. The company assumes no obligation to provide revisions to any forward-looking statements should circumstances change, except as otherwise required by securities and other applicable laws. © 2007 Huntsman Advanced Materials Switzerland. © Araldite is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more, but not all, countries.