



MOLYKOTE[®]
FROM DOW CORNING

Molykote[®] 1000 Paste

Proper tightening and corrosion prevention help to avoid bolt failure on wind turbines

Safe, reliable wind turbines depend on strong threaded connections.

Good lubrication of threaded connections can help to:

- Improve clamping force
- Tighten assembly bolts to required tension with correct torque
- Protect threaded connections for longer service life
- Allow easier disassembly

Molykote[®] 1000 Paste is suitable for threaded connections subjected to temperatures from -30°C (-22°F) to 650°C (1,202°F), as well as those that face such corrosive effects as pollution, rain, snow and salt fog.



AV14150

Molykote[®] 1000 Paste

Use *Molykote*[®] brand *Smart Lubrication*[™] solutions for strong threaded connections on:

- Nacelle frame joints
- Front and rear main journal bearings
- Pitch bearing fasten bolts
- Gearbox, drives and cooler units
- Yaw bearing fasten bolts
- Tower segment flange bolts
- Foundation anchor bolts



AV07765

As a solutions provider for the wind energy industry, Dow Corning offers high-performance specialty lubricants that are available globally, with consistent quality.

Contact us at wind.energy@dowcorning.com or visit molykote.com to learn how *Molykote*[®] 1000 Paste or other *Molykote*[®] brand or *Dow Corning*[®] brand solutions may be able to help you and your business.

Molykote[®] 1000 Paste is for industrial use only. For a material safety data sheet (MSDS) and other product details, including use and handling information, visit dowcorning.com.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Dow Corning is a registered trademark of Dow Corning Corporation.

Molykote is a registered trademark of Dow Corning Corporation.

Smart Lubrication is a trademark of Dow Corning Corporation.

©2010 Dow Corning Corporation. All rights reserved.

Printed in USA

AGP10772

Form No. 80-3462-01

DOW CORNING

Industrial Lubrication
Solutions