

---

**AC-9002****Light Mineral Filler**

Color: Gray

Density: 0.60-0.85 g/cm<sup>3</sup>

Bulk density: 0.35 – 0.4 g/cm<sup>3</sup>

Can be used with Epoxy and Polyurethane Systems

Packaging: 20 kg

---

---

**AC-9004****Inorganic Filler**

Color: White

Density: 2.4 g/cm<sup>3</sup>

Bulk density: 1.6 g/cm<sup>3</sup>

Can be used with Epoxy and Polyurethane Systems

Packaging: 20 kg, 1000 kg

---

---

**AC-9101****PVA Mold Sealer**

Film forming Poly-Vinyl-Alcohol (P.V.A.) release agent, which can also be used as sealer for porous surfaces.

Color: Green

Packaging: 4.5 kg

---

---

**AC-9102****Paste Release Agent**

Wax based release agent for general applications. Can be polished.

Color: White

Packaging: 12x1 kg

---

---

**AC-9103****Liquid Release Agent**

Wax based liquid release agent for the release of general and detailed mold surfaces. Can be polished.

Color: White

Packaging: 6x0.75 kg, 4x3.75 kg

---

---

### **Storage**

Original containers should be kept tightly sealed and stored at ambient temperatures (15°C to 30°C) in a dry place. If properly stored the products have the shelf-life indicated on the product label.

Partly used containers should always be sealed appropriately and used up as soon as possible.

---

---

### **Handling Precautions**

Good workplace ventilation is to be ensured during processing. At the same time, the employer's liability insurance association's industrial hygiene safety regulations regarding the handling of reaction resins and their hardeners are to be observed. Please take heed of the appropriate safety data sheets.

---